



C CONO

LED LIGHTING




DESCRIPTIONS

LED Recessed Downlight for indoor use. High performance effective lm/W. Maximum visual comfort. Structure material: Aluminium. Structure finish: White


SPECIFICATIONS

Mounting	Ceiling Recessed
Light Source	SMD LED
Material	Die cast Aluminum
Finish	White / Chrome
Body Color	White
Diffuser	PC Diffuser
CRI	Ra>80
Beam angle	60°
Power factor	>0.9
Ambient temperature	-20 °C ~ +45°C
Average Life Time (Hrs)	50,000 Hrs
Driver Mounting	Remote
Input Voltage/ Frequency	220-240V, 50/60Hz

DIMENSIONS



PHOTOMETRIC DATA



C CONO - Recessed Downlight



APPLICATION

Hotels, Residuals, Offices, Restaurants, General illumination.



CODE	Wattage	Gross Luminous Flux (lm)	Delivered Output (lm)	Color Temperature	Dimension ØxH (mm)	
RAY- C CONO-DL REC- 75- IP20- 5W	5W	500lm	400lm	3000K/ 4000K/ 6500K	Ø80*40	Ø75
RAY- C CONO-DL REC- 100- IP20- 9W	9W	900lm	750lm	3000K/ 4000K/ 6500K	Ø113*55	Ø100
RAY- C CONO-DL REC-140- IP20- 15W	15W	1650lm	1200lm	3000K/ 4000K/ 6500K	Ø165*74	Ø140
RAY- C CONO-DL REC- 170- IP20- 20W	20W	2000lm	1800lm	3000K/ 4000K/ 6500K	Ø195*85	Ø170
RAY- C CONO-DL REC- 200- IP20- 30W	30W	3000lm	2500lm	3000K/ 4000K/ 6500K	Ø228*97	Ø200

* On/Off Remote driver Included as a standrd, 0-10 and DALI dimmable Driver as an optional.

** Available 3 hours emergency kit as an optional