



الباطين للطاقة و الاتصالات  
AL-BABTAIN POWER & TELECOM



# CONFORTO

LED LIGHTING




## DESCRIPTIONS

LED Recessed Downlight for indoor use. High performance effective lm/W. Maximum visual comfort. Structure material: Aluminium. Structure finish: White


## SPECIFICATIONS

Mounting	Ceiling Recessed
Light Source	COB LED
Material	Die cast Aluminum
Finish	White / Chrome
Body Color	White
Diffuser	PC Diffuser
CRI	Ra>80
Beam angle	15°, 24°, 45°
Power factor	>0.5
Ambient temperature	-20 °C ~ +45°C
Average Life Time (Hrs)	50,000 Hrs
Driver Mounting	Remote
Input Voltage/ Frequency	220-240V, 50/60Hz

## DIMENSIONS



## PHOTOMETRIC DATA



## CONFORTO-IP - Recessed Downlight



## APPLICATION

Hotels, Residentials, Offices, Restaurants, General illumination.



CODE	Wattage	Gross Luminous Flux (lm)	Delivered Output (lm)	Color Temperature	Dimension ØxH (mm)	
RAY- CONFORTO-DL REC- 75- IP44-8W	8W	1000lm	800lm	3000K/ 4000K/ 6500K	Ø80*66	Ø66

\* On/Off Remote driver Included as a standrd, 0-10 and DALI dimmable Driver as an optional.

\*\* Available 3 hours emergency kit as an optional