





CORON

LED LIGHTING





البابطيــن للطاقة و الاتصالات AL-BABTAIN POWER & TELECOM

#### DESCRIPTIONS

CORON is a garden spot light, IP67 ,LED 15W

**CORON** - Spotlight

#### **SPECIFICATIONS**

Mounting	Surface
Light Source	LED
Material	Aluminum
CRI	Ra>80
Beam angle	25°, 38°, 60°
Ambient temperature	-20°C ~ +50°C
Average Life Time (Hrs)	50,000 Hrs
Driver Mounting	Integrated Driver
Input Voltage/ Frequency	220-240V, 50/60Hz











50°C


IK04

#### **APPLICATION**


Outdoor



## **DIMENSIONS**



## PHOTOMETRIC DATA



CODE	Wattage	Delivered Output (lm)	Color Temperature	Dimension (mm)	<b>₽</b>
RAY -CORON-SPK-75-IP67-15W	15W	1350lm	2700K/ 3000K/ 4000K	as per drawing	N/A





# Pole for garden spot lights:





	,		1
Specie	cations	Dimension	
ltem	Pole-300 with base		@25mm
	Ø25mm x 300mm (Diameter x height ) , Aluminium anodizing + powder coated painting in dark grey as		ПТ
Pole	standard, black as optional		
_	Ø75mm SS304 round base as optional for concrete ground installation, painted in dark grey as standard,	(EX	Difference 2x cot.5
Base	black color as optoins	0	
		Round be	
Specie	cations	Dimension	
ltem	Pole-300 with spike and pedal		885mm
	Ø25mm x 300mm (Diameter x height ) , Aluminium anodizing + powder coated painting in dark grey as		ПТ
Pole	standard, black as optional		II I
Spike	With Aluminium spike powder coated painting in dark grey as standard, black color as options 205 mm height		@
Pedal	SS304 Pedal that can be used with spike for pushing the spike light into the ground by foot	+	<del>n</del>
			<b>∦</b> ∦
Specie	cations	Dimension	' '
ltem	Pole-500 with base		El T
Pole	Ø25mm x 500mm (Diameter x height ) , Aluminium anodizing + powder coated painting in dark grey as		
. 0.0	standard, black as optional		
Base	Ø75mm SS304 round base as optional for concrete ground installation, painted in dark grey as standard,	(O)	700 mm 3x 004.5
	black color as optoins	Round be	
Specie	cations	Dimension	• 🖶 ڶ
ltem	Pole-500 with spike and pedal		805mm
	Ø25mm x 500mm (Diameter x height ) , Aluminium anodizing + powder coated painting in dark grey as		ĬĪ
Pole	standard, black as optional		III III
Spike	With Aluminium spike powder coated painting in dark grey as standard, black color as options 205 mm height		100
Pedal	SS304 Pedal that can be used with spike for pushing the spike light into the ground by foot	1	# # <sup>1</sup>
			₩ ₩
Specie	cations	Dimension	
ltem	Pole-750 with base		825mm 
Pole	Ø25mm x 750mm (Diameter x height ) , Aluminium anodizing + powder coated painting in dark grey as		ПТ
	standard, black as optional		
Bacc	Ø75mm SS304 round base as optional for concrete ground installation, painted in dark grey as standard,	(A)	700 3x 04.5
Base	black color as optoins	Round be	
		E B75mar	<u> </u>
Specie	cations	Dimension	
ltem	Pole-750 with spike and pedal		005mm
	COS 750 ID: A LALL AL		[] [

standard, black as optional

 $\emptyset$ 25mm x 750mm (Diameter x height ) , Aluminium anodizing + powder coated painting in dark grey as

 Spike
 With Aluminium spike powder coated painting in dark grey as standard, black color as options 205 mm height

 Pedal
 SS304 Pedal that can be used with spike for pushing the spike light into the ground by foot