



DAMP LED 2

LED LIGHTING



DESCRIPTIONS

DAMP LED 2 Generally used for industrial environment with corrosive, dusty, damp, outdoor or semi outdoor environment, Reduction in over all height, with built in driver.

DAMP LED 2 - Industrial Light

SPECIFICATIONS

Mounting	Surface and Suspended
Light Source	SMD LED
Material	Polycarbonate (PC)
Body Color	Grey
Diffuser	PC Diffuser
CRI	Ra>80
Beam angle	110°
Power factor	>0.9
Ambient temperature	-20 °C ~ +50°C
Average Life Time (Hrs)	50,000 Hrs
Driver Mounting	Built-in
Input Voltage/ Frequency	220-240V, 50/60Hz




APPLICATION


Industrial, Assembly Lines, Workshops, Parking, Electrical Rooms.



DIMENSIONS



PHOTOMETRIC DATA



CODE	Wattage	Gross Luminous Flux (lm)	Delivered Output (lm)	Color Temperature	Dimension WxHxL (mm)	
RAY-DAMP LED 2-SUR -600MM-IP65-22W	22W	2800lm	2640lm	3000K/ 4000K/ 6500K	127* 86* 650	N/A
RAY-DAMP LED 2-SUR -1200MM-IP65-48W	48W	6200lm	5760lm	3000K/ 4000K/ 6500K	127* 86* 1260	N/A
RAY-DAMP LED 2-SUR -1500MM-IP65-55W	55W	7000lm	6600lm	3000K/ 4000K/ 6500K	127* 86* 1560	N/A

* On/Off built-in driver as a standard, 0-10 and DALI dimmable Driver as an optional.

** Available 3 hours emergency kit as an optional