

BL R2

LED LIGHTING




DESCRIPTIONS

BL R2 is a Recessed LED backlight panel, with long lifespan upto 50,000Hrs, It is perfect replacement for traditional lighting.


SPECIFICATIONS

Mounting	Recessed
Light Source	SMD LED
Material	Aluminum
Body Color	White
Diffuser	PC Diffuser
CRI	Ra>80
Beam angle	Very Wide
Power factor	>0.9
Ambient temperature	-20 °C ~ +45°C
Average Life Time (Hrs)	50,000 Hrs
Driver Mounting	Remote
Input Voltage/ Frequency	220-240V, 50/60Hz

DIMENSIONS



PHOTOMETRIC DATA



BL R2 - LED Panel Light



APPLICATION

Offices, Hospitals, Schools, Residential Buildings, and other General illumination.



CODE	Wattage	Gross Luminous Flux (lm)	Delivered Output (lm)	Color Temperature	Dimension HxL (mm)	
RAY-BL R2-REC PAN-30X120-IP40-40W	40W	4350lm	4000lm	3000K/ 4000K/ 6500K	295*1195	N/A
RAY-BL R2-REC PAN-60X120-IP40-50W	50W	7000lm	6000lm	3000K/ 4000K/ 6500K	595*1195	N/A

* On/Off Remote driver Included as a standrd, 0-10 and DALI dimmable Driver as an optional.

** Available 3 hours emergency kit as an optional