









BKH1 - LED Ceiling Light

DESCRIPTIONS

BKH 1 is a Modern design for wall or ceiling applications,

Professional optical design for uniform light distribution,

This luminaire that is ideal for corridors, communal areas or stairs .

SPECIFICATIONS

Mounting	Surface ceiling / Wall Luminaire		
Light Source	SMD LED		
Material	PC		
Finish	White / White, White		
Body Color	White		
Diffuser	PMMA		
CRI	Ra>80		
Beam angle	110°		
Power factor	>0.9		
Ambient temperature	-20°C ~ +45°C		
Average Life Time (Hrs)	50,000 Hrs		
Driver Mounting	Built-in		
Input Voltage/ Frequency	220-240V, 50/60Hz		


















APPLICATION


Hotels, residential, Offices, restaurants, General illumination.



DIMENSIONS



PHOTOMETRIC DATA



CODE	Wattage	Gross Luminous Flux (lm)	Delivered Output (lm)	Color Temperature	Dimension ØxH (mm)	₽
RAY-BKH1-SUR DL-300MM-IP65-18W	10W, 14W,18W	2000lm	1800lm	3000K/ 4000K	300*60	N/A

^{*} Changing power by Dip switch.

^{**} Available 3 hours emergency kit as an optional.