





ARMONA

LED LIGHTING





البابطيــن للطاقة و الاتصالات AL-BABTAIN POWER & TELECOM

DESCRIPTIONS

ARMONA is outdoor wall fixture for uplighting and downligting. Structure material: High purity aluminium. Structure finish: Diffuser material: Clear tempered glass.

SPECIFICATIONS

Mounting	Surface Wall Mounted		
Wounting	Surface Wall Mounted		
Light Source	LED		
Material	Die-casting Aluminum Alloy		
Body Color	Black as Standard		
Diffuser	Clear tempered glass		
CRI	Ra>80		
Beam angle	2×15°		
Ambient temperature	-20°C ~ +50°C		
Average Life Time (Hrs)	50,000 Hrs		
Driver Mounting	Integrated driver		
Input Voltage/ Frequency	220-240V, 50/60Hz		

ARMONA -Wall Mounted









IP65

50°C

IK06



APPLICATION

Outdoor and Indoor etc...

DIMENSIONS



PHOTOMETRIC DATA





CODE	Wattage	Delivered Output (lm)	Color Temperature	Dimension (mm)	de la
RAY -ARMONA-UP DWN-IP65-2X20W	2x20W	2050lm	3000K/ 4000K	140* 300* 175	N/A