



الباطين للطاقة و الاتصالات
AL-BABTAIN POWER & TELECOM



COBRA
LED LIGHTING



DESCRIPTIONS

Cobra Series has the characteristics of diversity, aesthetics and beautification and decoration of the environment. It is mainly used for outdoor lighting in urban slow lane and narrow lane residential communities.

SPECIFICATIONS

Mounting	Post-top
Light Source	LED
Material	Die cast aluminum
Finish	Polyester powder coatings
Body Color	Matte Black, White, Bronze
Diffuser	PC Diffuser
CRI	Ra>70
Light distribution	Type II, Type III, Type IV, Type V
Power factor	>0.9
Operating temp (°C)	-40°C ~ +55°C
Average Life Time (Hrs)	50,000 Hrs
Driver Mounting	Built-in
Input Voltage/ Frequency	220-240V, 50/60Hz

COBRA - Post-top



CB

CE

IP65

55°C

IK08



APPLICATION


Garden, Park, Pathway, Road etc...



DIMENSIONS



PHOTOMETRIC DATA



CODE	Wattage	Delivered Output (lm)	Color Temperature	Dimension ØxH (mm)	
RAY- CORDOBA- URB-PT- LTYL-909A- IP65	30W/ 60W/ 100W/ 50W	3600lm / 7200lm / 12000lm / 18000lm	4000K/ 5700K	Ø19.2* 24.3	N/A
RAY- CORDOBA- URB-PT- LTYL-909B- IP65	30W/ 60W/ 100W/ 50W	3600lm / 7200lm / 12000lm / 18000lm	4000K/ 5700K	Ø19.2* 24.3	N/A
RAY- CORDOBA- URB-PT- LTYL-909C- IP65	30W/ 60W/ 100W/ 50W	3600lm / 7200lm / 12000lm / 18000lm	4000K/ 5700K	Ø18.9* 22	N/A


* On/Off Built-in driver Included as a standard, 0-10 and DALI dimmable Driver as an optional.

** Available 3 hours emergency kit as an optional

COBRA - Post-top



Dimension Drawings



Installation

