



البابطين للطاقة و الاتصالات
AL-BABTAIN POWER & TELECOM



TACORA
LED LIGHTING



DESCRIPTIONS

TACORA is a decorative luminaire for outdoor use .Inspired by the form of a typical residential luminaire, It acts as a distinctiv eye-catcher in urban areas. It is ideal for give a wonderful and warm ambience. TACORA is available in two version as bracket mounted luminaire or a suspension version.

SPECIFICATIONS

Mounting	Bracket mounted luminaire
Light Source	LED
Material	Aluminum head & heatsink ,PMMA diffuser
Diffuser	PMMA diffuser
CRI	Ra>80
Beam angle	Very wide
Power factor	>0.9
Ambient temperature	-20 °C ~ +50°C
Average Life Time (Hrs)	50,000 Hrs
Driver Mounting	Electronic LED driver
Input Voltage/ Frequency	220-240V, 50/60Hz

TACORA - bracket mounted luminaire




APPLICATION


Outdoor



DIMENSIONS



PHOTOMETRIC DATA



CODE	Wattage	Delivered Output (lm)	Color Temperature	Dimension ØxH (mm)	
RAY -TACORA-URB-IP65-44W	44W	3200lm	3000K/ 4000K	Ø460* 435	N/A
RAY -TACORA-URB-IP65-44W(suspension)	44W	3200lm	3000K/ 4000K	Ø460* 435	N/A